	<b>SAFETY DATA SHEET</b>	Page : 1 / 14
		Revision nr : 1.1
	<b>Storage Seal - Fogging Oil</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form : Mixtures  
Trade name/designation : Storage Seal - Fogging Oil  
Product code : 92-858081Q03, 92-8M0121972  
Vaporizer : Aerosol  
Document no. : 766-01-0138S

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Industrial use, Professional uses, Consumer use  
Use of the substance/mixture : Aerosol  
Corrosion inhibitor

#### 1.2.2. Uses advised against

No data available

### 1.3. Details of the supplier of the safety data sheet

Brunswick Marine EMEA  
Parc industriel de Petit-Rechain, Avenue Mercury 8  
4800 Verviers - Belgium  
T +32 (0)87 32 32 11  
[bme.compliance@brunswick.com](mailto:bme.compliance@brunswick.com)

### 1.4. Emergency telephone number

Emergency number : 0032 3 575 55 55  
This telephone number is available 24 hours per day, 7 days per week.

Country	Official advisory body	Address	Emergency number
Ireland	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	+353 1 809 21 66 (public, 8am - 10pm, 7/7) +353 01 809 2566 (Professionals, 24/7)
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours, healthcare professionals only)


## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229  
Skin Sens. 1 H317  
Aquatic Chronic 3 H412

Full text of hazard classes and H-statements : see section 16

	<b>SAFETY DATA SHEET</b>	Page : 2 / 14
		Revision nr : 1.1
	<b>Storage Seal - Fogging Oil</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word :

Danger

Hazardous ingredients :

Calcium sulfonates

Hazard statements (CLP) :

H222 - Extremely flammable aerosol.  
H229 - Pressurised container: May burst if heated.  
H317 - May cause an allergic skin reaction.  
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP) :

P101 - If medical advice is needed, have product container or label at hand.  
P102 - Keep out of reach of children.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 - Do not spray on an open flame or other ignition source.  
P251 - Do not pierce or burn, even after use.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
P501 - Dispose of contents/container to an approved waste disposal plant.

## 2.3. Other hazards

Other hazards :

Vapours may form explosive mixture with air. Results of PBT and vPvB assessment : Not applicable.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable


### 3.2. Mixtures

Comments :

Aerosol

Substance name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium sulfonates	(CAS-No.) 64521-08-0	5 - 10	Skin Sens. 1, H317 Aquatic Chronic 2, H411
propane	(CAS-No.) 74-98-6 (EC-No.) 200-827-9 (EC Index) 601-003-00-5	2 - 6	Flam. Gas 1, H220 Press. Gas (Liq.), H280
butane	(CAS-No.) 106-97-8 (EC-No.) 203-448-7 (EC Index) 601-004-00-0	1 - 5	Flam. Gas 1, H220 Press. Gas (Liq.), H280

Full text of H-statements: see section 16

	<b>SAFETY DATA SHEET</b>	Page : 3 / 14
	<b>Storage Seal - Fogging Oil</b>	Revision nr : 1.1
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Additional advice	: First aider: Pay attention to self-protection. Concerning personal protective equipment to use, see section 8. Never give anything by mouth to an unconscious person or a person with cramps. In case of doubt or persistent symptoms, consult always a physician. Show this safety data sheet to the doctor in attendance. Treat symptomatically.
Inhalation	: Remove person to fresh air and keep comfortable for breathing. In case of doubt or persistent symptoms, consult always a physician.
Skin contact	: Take off contaminated clothing. Gently wash with plenty of soap and water. In case of doubt or persistent symptoms, consult always a physician.
Eyes contact	: Rinse immediately with plenty of water. In case of doubt or persistent symptoms, consult always a physician.
Ingestion	: Rinse mouth out with water. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Inhalation	: No adverse effects are expected.
Skin contact	: May cause an allergic skin reaction.
Eyes contact	: No adverse effects are expected.
Ingestion	: The following symptoms may occur: May cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available

## SECTION 5: Fire-fighting measures

### 5.1. Extinguishing media


Suitable extinguishing media	: Water spray. Alcohol resistant foam. dry extinguishing powder. Carbon dioxide.
Unsuitable extinguishing media	: Strong water jet.

### 5.2. Special hazards arising from the substance or mixture

Specific hazards	: Extremely flammable aerosol. Ignition risk. Vapours are heavier than air and may spread along floors. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Aerosol cans may rupture and become projectiles. In use, may form flammable/explosive vapour-air mixture. Do not spray on a naked flame or any incandescent material. On heating there is a risk of a build-up of pressure in hermetically sealed containers or tanks.
Hazardous decomposition products in case of fire	: Carbon oxides (CO, CO <sub>2</sub> ).

### 5.3. Advice for firefighters

Firefighting instructions	: Evacuate area. Use water spray or fog for cooling exposed containers. Contain the extinguishing fluids by bunding. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus.
Other information	: Do not allow run-off from fire-fighting to enter drains or water courses.

	<b>SAFETY DATA SHEET</b>	Page : 4 / 14
	<b>Storage Seal - Fogging Oil</b>	Revision nr : 1.1
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

For non-emergency personnel : Evacuate personnel to a safe area. Stay upwind/keep distance from source. Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof equipment. Use only non-sparking tools.

#### 6.1.2. For emergency responders

For emergency responders : Ensure procedures and training for emergency decontamination and disposal are in place. Concerning personal protective equipment to use, see section 8.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Notify authorities if product enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Leave evaporate and disperse. Clean-up methods - small spillage: Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite or powdered limestone. Collect in closed and suitable containers for disposal. Dispose of waste product or used containers according to local regulations.

### 6.4. Reference to other sections

Concerning personal protective equipment to use, see section 8. Concerning disposal elimination after cleaning, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Provide adequate ventilation. Use personal protective equipment as required. Concerning personal protective equipment to use, see section 8. Do not breathe vapour/aerosol. Avoid contact with skin, eyes and clothing. Take any precaution to avoid mixing with combustibles/... See also section 10. Ensure proper process control to avoid excess waste discharge (temperature, concentration, pH, time). Do not allow to enter into surface water or drains. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurised container. May burst if heated.

#### Hygiene measures

: Keep good industrial hygiene. Wash hands immediately after handling the product. When using do not eat, drink or smoke. Keep away from food, drink and animal feedingstuffs. Separate working clothes from town clothes. Take off contaminated clothing. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Flammable aerosols. Store in a dry, cool and well-ventilated place. Refer to the detailed list of incompatible materials in section 10 Stability/Reactivity. Bund storage facilities to prevent soil and water pollution in the event of spillage. Protect from sunlight. Remove all sources of ignition. Keep at temperature not exceeding 50.

#### Packaging materials

: Keep only in the original container.

### 7.3. Specific end use(s)

No data available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

propane (74-98-6)		
Austria	MAK (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Austria	MAK (ppm)	1000 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	3600 mg/m <sup>3</sup>

## Storage Seal - Fogging Oil

**propane (74-98-6)**

Austria	MAK Short time value (ppm)	2000 ppm
Belgium	Limit value (ppm)	1000 ppm (gas)
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Estonia	OEL TWA (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	1000 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	1500 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	800 ppm
Finland	HTP-arvo (15 min)	2000 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	1100 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Greece	OEL TWA (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	1000 ppm
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	OEL (15 min ref) (ppm)	3000 ppm (calculated)
Latvia	OEL TWA (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	1000 ppm
Poland	NDS (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Portugal	OEL TWA (ppm)	1000 ppm
Romania	OEL TWA (mg/m <sup>3</sup> )	1400 mg/m <sup>3</sup>
Romania	OEL TWA (ppm)	778 ppm
Romania	OEL STEL (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Romania	OEL STEL (ppm)	1000 ppm
Slovenia	OEL TWA (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	1000 ppm
Slovenia	OEL STEL (mg/m <sup>3</sup> )	7200 mg/m <sup>3</sup>
Slovenia	OEL STEL (ppm)	4000 ppm
Norway	Grænseverdier (AN) (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Norway	Grænseverdier (AN) (ppm)	500 ppm
Norway	Grænseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	1125 mg/m <sup>3</sup> (value calculated)
Norway	Grænseverdier (Korttidsverdi) (ppm)	625 ppm (value calculated)
Switzerland	VME (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Switzerland	VME (ppm)	1000 ppm
Switzerland	VLE (mg/m <sup>3</sup> )	7200 mg/m <sup>3</sup>
Switzerland	VLE (ppm)	4000 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	1000 ppm
USA - IDLH	US IDLH (ppm)	2100 ppm (10% LEL)
USA - NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
USA - NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm


## Storage Seal - Fogging Oil

**propane (74-98-6)**

USA - OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm

**butane (106-97-8)**

Austria	MAK (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Austria	MAK (ppm)	800 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	3800 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	1600 ppm
Belgium	Limit value (ppm)	1000 ppm (gas)
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	1450 mg/m <sup>3</sup> 22 mg/m <sup>3</sup> (containing >=0.1% 1,3-Butadiene)
Croatia	GVI (granična vrijednost izloženosti) (ppm)	600 ppm 10 ppm (containing >=0.1% 1,3-Butadiene)
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	1810 mg/m <sup>3</sup>
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	750 ppm
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	1200 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	500 ppm
Estonia	OEL TWA (mg/m <sup>3</sup> )	1500 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	800 ppm
Finland	HTP-arvo (8h) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Finland	HTP-arvo (8h) (ppm)	800 ppm
Finland	HTP-arvo (15 min)	2400 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	1000 ppm
France	VME (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
France	VME (ppm)	800 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Greece	OEL TWA (mg/m <sup>3</sup> )	2350 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	1000 ppm
Hungary	AK-érték	2350 mg/m <sup>3</sup>
Hungary	CK-érték	9400 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	OEL (15 min ref) (ppm)	3000 ppm (calculated)
Latvia	OEL TWA (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
Poland	NDS (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	3000 mg/m <sup>3</sup>
Slovenia	OEL TWA (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup> (containing >=0.1% Butadiene)
Slovenia	OEL TWA (ppm)	1000 ppm (containing >=0.1% Butadiene)
Slovenia	OEL STEL (mg/m <sup>3</sup> )	9600 mg/m <sup>3</sup> (containing >=0.1% Butadiene)
Slovenia	OEL STEL (ppm)	4000 ppm (containing >=0.1% Butadiene)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	1450 mg/m <sup>3</sup>

	<b>SAFETY DATA SHEET</b>	Page : 7 / 14
		Revision nr : 1.1
	<b>Storage Seal - Fogging Oil</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

<b>butane (106-97-8)</b>		
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	1810 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	750 ppm
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	250 ppm
Norway	Grenseverdier (Korttidsverdi) (mg/m <sup>3</sup> )	750 mg/m <sup>3</sup> (value calculated)
Norway	Grenseverdier (Korttidsverdi) (ppm)	312,5 ppm (value calculated)
Switzerland	VME (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Switzerland	VME (ppm)	800 ppm
Switzerland	VLE (mg/m <sup>3</sup> )	7600 mg/m <sup>3</sup>
Switzerland	VLE (ppm)	3200 ppm
Australia	TWA (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Australia	TWA (ppm)	800 ppm
Canada (Quebec)	VEMP (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
Canada (Quebec)	VEMP (ppm)	800 ppm
USA - ACGIH	ACGIH STEL (ppm)	1000 ppm
USA - NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	1900 mg/m <sup>3</sup>
USA - NIOSH	NIOSH REL (TWA) (ppm)	800 ppm


## **8.2. Exposure controls**

Engineering measure(s)	: Provide adequate ventilation. Organisational measures to prevent /limit releases, dispersion and exposure. Safe handling: see section 7 . Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges.
Personal protective equipment	: The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Hand protection	: Chemical resistant gloves (according to European standard NF EN 374 or equivalent). Suitable material: The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.
Eye protection	: Use suitable eye protection (EN166): Safety glasses
Body protection	: Wear suitable protective clothing
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Half-face mask (DIN EN 140). full face mask (DIN EN 136). Filter type: ABEK + P. The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used. (EN 137)
Thermal hazard protection	: Not required for normal conditions of use. Use dedicated equipment.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

Physical state	: liquid
Appearance	: aerosol.
Colour	: No data available.
Odour	: No data available.
Odour threshold	: No data available
pH	: No data available

	<b>SAFETY DATA SHEET</b>	Page : 8 / 14
		Revision nr : 1.1
	<b>Storage Seal - Fogging Oil</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

Relative evaporation rate (butylacetate=1) : No data available  
Melting / freezing point : No data available  
Freezing point : No data available  
Initial boiling point and boiling range : No data available  
Flash point : No data available  
Auto-ignition temperature : No data available  
Decomposition temperature : No data available  
Flammability (solid, gas) : Extremely flammable aerosol.  
Vapour pressure : No data available  
Vapour density : No data available  
Relative density : No data available  
Solubility : No data available.  
Water: No data available  
Partition coefficient n-octanol/water : No data available  
Kinematic viscosity : No data available  
Dynamic viscosity : No data available  
Explosive properties : No data available.  
Oxidising properties : No data available.  
Explosive limits : No data available

**9.2. Other information**

No data available

**SECTION 10: Stability and reactivity**

**10.1. Reactivity**

Extremely flammable aerosol. Reference to other sections 10.4 & 10.5.

**10.2. Chemical stability**

The product is stable under storage at normal ambient temperatures.

**10.3. Possibility of hazardous reactions**

Will ignite if exposed to intensive heat and air. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

**10.4. Conditions to avoid**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid temperature above 50.  
Safe handling: see section 7.

**10.5. Incompatible materials**

oxidising substances. Safe handling: see section 7.

**10.6. Hazardous decomposition products**

Reference to other sections 5.2.

**SECTION 11: Toxicological information**


**11.1. Information on toxicological effects**

Acute toxicity : Not classified (Based on available data, the classification criteria are not met.)

<b>propane (74-98-6)</b>	
LC50/inhalation/4h/rat	658 mg/l/4h
<b>butane (106-97-8)</b>	
LC50/inhalation/4h/rat	658 g/m <sup>3</sup> (Exposure time: 4 h)

Skin corrosion/irritation : Not classified (Based on available data, the classification criteria are not met.)  
pH: No data available



	<b>SAFETY DATA SHEET</b>	Page : 9 / 14
	<b>Storage Seal - Fogging Oil</b>	Revision nr : 1.1
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

Serious eye damage/irritation : Not classified (Based on available data, the classification criteria are not met.)  
pH: No data available

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met.)

Carcinogenicity : Not classified (Based on available data, the classification criteria are not met.)

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met.)

STOT-single exposure : Not classified (Based on available data, the classification criteria are not met.)

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met.)

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met.)

<b>Storage Seal - Fogging Oil</b>	
Vaporizer	Aerosol

Other information : Symptoms related to the physical, chemical and toxicological characteristics. For further information see section 4.

## SECTION 12: Ecological information

### 12.1. Toxicity

Environmental properties : Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

<b>Storage Seal - Fogging Oil</b>	
Persistence and degradability	No data available.

### 12.3. Bioaccumulative potential

<b>Storage Seal - Fogging Oil</b>	
Partition coefficient n-octanol/water	No data available

#### propane (74-98-6)

Partition coefficient n-octanol/water	2,3
---------------------------------------	-----

#### butane (106-97-8)

Partition coefficient n-octanol/water	2,89
---------------------------------------	------

### 12.4. Mobility in soil

<b>Storage Seal - Fogging Oil</b>	
Ecology - soil	No data available.

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.6. Other adverse effects


Additional information : No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product/Packaging disposal recommendations : Do not allow to enter into surface water or drains. Dispose of empty containers and wastes safely. Safe handling: see section 7. Refer to manufacturer/supplier for information on recovery/recycling. Recycling is preferred to disposal or incineration. If recycling is not possible, eliminate in accordance with local valid waste disposal regulations.






Additional information : Never use pressure to empty container. Handle contaminated packages in the same way as the substance itself. Dispose of contaminated materials in accordance with current regulations. Do not burn, or use a cutting torch on, the empty drum. Do not puncture or incinerate.

	<b>SAFETY DATA SHEET</b>	Page : 10 / 14
		Revision nr : 1.1
	<b>Storage Seal - Fogging Oil</b>	Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

European waste catalogue (2001/573/EC, 75/442/EEC, 91/689/EEC) : This material and its container must be disposed of as hazardous waste  
Waste codes should be assigned by the user based on the application for which the product was used.

**SECTION 14: Transport information**

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number</b>				
1950	1950	1950	1950	1950
<b>14.2. UN proper shipping name</b>				
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
<b>Transport document description</b>				
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.1
<b>14.3. Transport hazard class(es)</b>				
2.1	2.1	2.1	2.1	2.1
				
<b>14.4. Packing group</b>				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
<b>14.5. Environmental hazards</b>				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Dangerous for the environment : No	Dangerous for the environment : No
No supplementary information available				

**14.6. Special precautions for user**


Special precautions for user : No data available

**- Overland transport**

Classification code (ADR) : 5F  
 Special provisions : 190, 327, 344, 625  
 Limited quantities (ADR) : 1I  
 Excepted quantities (ADR) : E0  
 Packing instructions (ADR) : P207, LP02  
 Special packing provisions (ADR) : PP87, RR6, L2  
 Mixed packing provisions (ADR) : MP9  
 Transport category (ADR) : 2  
 Special provisions for carriage - Packages (ADR) : V14  
 Special provisions for carriage - Loading, unloading and handling (ADR) : CV9, CV12  
 Special provisions for carriage - Operation (ADR) : S2  
 Tunnel restriction code : D

**- Transport by sea**

Special provisions (IMDG) : 63, 190, 277, 327, 344, 959  
 Limited quantities (IMDG) : SP277  
 Excepted quantities (IMDG) : E0

	<b>SAFETY DATA SHEET</b>	Page : 11 / 14
	<b>Storage Seal - Fogging Oil</b>	Revision nr : 1.1
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

Packing instructions (IMDG) : P207, LP02  
Special packing provisions (IMDG) : PP87, L2  
EmS-No. (Fire) : F-D  
EmS-No. (Spillage) : S-U  
Stowage category (IMDG) : None

**- Air transport**

PCA Excepted quantities (IATA) : E0  
PCA Limited quantities (IATA) : Y203  
PCA limited quantity max net quantity (IATA) : 30kgG  
PCA packing instructions (IATA) : 203  
PCA max net quantity (IATA) : 75kg  
CAO packing instructions (IATA) : 203  
CAO max net quantity (IATA) : 150kg  
Special provisions (IATA) : A145, A167  
ERG code (IATA) : 10L

**- Inland waterway transport**

Classification code (ADN) : 5F  
Special provisions (ADN) : 19, 327, 344, 625  
Limited quantities (ADN) : 1 L  
Excepted quantities (ADN) : E0  
Equipment required (ADN) : PP, EX, A  
Ventilation (ADN) : VE01, VE04  
Number of blue cones/lights (ADN) : 1

**- Rail transport**

Classification code (RID) : 5F  
Special provisions (RID) : 190, 327, 344, 625  
Limited quantities (RID) : 1L  
Excepted quantities (RID) : E0  
Packing instructions (RID) : P207, LP02  
Special packing provisions (RID) : PP87, RR6, L2  
Mixed packing provisions (RID) : MP9  
Transport category (RID) : 2  
Special provisions for carriage – Packages (RID) : W14  
Special provisions for carriage - Loading, unloading and handling (RID) : CW9, CW12  
Colis express (express parcels) (RID) : CE2  
Hazard identification number (RID) : 23

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**


Not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**15.1.1. EU-Regulations**

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

	<b>SAFETY DATA SHEET</b>	Page : 12 / 14
	<b>Storage Seal - Fogging Oil</b>	Revision nr : 1.1
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	Storage Seal - Fogging Oil
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	Storage Seal - Fogging Oil
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	Storage Seal - Fogging Oil
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Storage Seal - Fogging Oil
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	propane - butane

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

#### 15.1.2. National regulations

France

Installations classées :

Not applicable.

#### Germany

VwVwS Annex reference : Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)

German storage class (LGK) : LGK 2B - Aerosols

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

#### Netherlands

Waterbezwaarlijkheid : 8 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Saneringsinspanningen : A - In principe niet lozen; zo ja, dan toepassen van beste bestaande technieken

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed


NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

#### Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

#### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

	<b>SAFETY DATA SHEET</b>	Page : 13 / 14
	<b>Storage Seal - Fogging Oil</b>	Revision nr : 1.1
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

## SECTION 16: Other information

Indication of changes:

1	Identification of the substance/mixture and of the company/undertaking	Modified	
1	Product code	Modified	
1.1	Trade name/designation	Modified	
2	DSD/DPD	Removed	
3	DSD/DPD	Removed	
5	Fire-fighting measures	Modified	
11	Information on toxicological effects	Modified	
14	Transport information	Modified	
15.1	National regulations	Modified	
16	Other information	Modified	

Abbreviations and acronyms:


	ABM = Algemene beoordelingsmethodiek
	ADN = Accord Européen relatif au Transport International des Marchandises Dangereuses par voie de Navigation du Rhin
	ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
	CLP = Classification, Labelling and Packaging Regulation according to 1272/2008/EC
	IATA = International Air Transport Association
	IMDG = International Maritime Dangerous Goods Code
	LEL = Lower Explosive Limit/Lower Explosion Limit
	UEL = Upper Explosion Limit/Upper Explosive Limit
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
	BTT = Breakthrough time :
	DMEL = Derived Minimal Effect level
	DNEL = Derived No Effect Level
	EC50 = Median Effective Concentration
	EL50 = Median effective level
	ErC50 = EC50 in terms of reduction of growth rate
	ErL50 = EL50 in terms of reduction of growth rate
	EWC = European waste catalogue
	LC50 = Median lethal concentration
	LD50 = Median lethal dose
	LL50 = Median lethal level
	NA = Not applicable
	NOEC = No observed effect concentration
	NOEL: no-observed-effect level
	NOELR = No observed effect loading rate
	NOAEC = No observed adverse effect concentration
	NOAEL = No observed adverse effect level
	N.O.S. = Not Otherwise Specified
	OEL = Occupational Exposure Limits - Short Term Exposure Limits (STELs)
	PNEC = Predicted No-Effect Concentration
	Quantitative structure-activity relationship (QSAR)
	STOT = Specific Target Organ Toxicity
	TWA = time weighted average
	VOC = Volatile organic compounds (VOC) :
	WGK = Wassergefährdungsklasse (Water Hazard Class under German Federal Water Management Act)

Sources of key data used to compile the datasheet : ECHA, MSDS (Supplier), Loli.

Training advice : Training staff on good practice.

Other information : Assessment/classification CLP. Article 9. Calculation method.

Full text of H- and EUH-statements:

	<b>SAFETY DATA SHEET</b>	Page : 14 / 14
	<b>Storage Seal - Fogging Oil</b>	Revision nr : 1.1
		Issue date : 24/02/2017
		Supersedes : 25/03/2015
		<b>766-01-0138S</b>

Aerosol 1	Aerosol, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - chronic hazard category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - chronic hazard category 3
Flam. Gas 1	Flammable gases, hazard category 1
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Sens. 1	Skin sensitisation, hazard category 1
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container. May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

According to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830  
Classification according to Regulation (EC) No. 1272/2008 [CLP]  
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

**DISCLAIMER OF LIABILITY** The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.